TABLE OF CONTENTS

- 1. AVAILABLE COVER PROFILE
 - 1.1. THERM+ H-I 56mm

2. DETAILS OF TYPICAL SYSTEMS

- 2.1. THERM+ H-I 56/60mm
 - 2.1.1. Cover profile Double glazing
 - 2.1.2. Cover profile Triple glazing
 - 2.1.3. Wood cover profile Double glazing
 - 2.1.4. Wood cover profile Triple glazing
 - 2.1.5. Detail of perimeter system
 - 2.1.6. SG2 system
 - 2.1.6.1. Without suction disc
 - 2.1.6.2. With suction disc Round Double glazing
 - 2.1.6.3. With suction disc Round Triple glazing
 - 2.1.6.4. With suction disc Double glazing
 - 2.1.6.5. With suction disc Triple glazing
 - 2.1.7. Typical Spandrel panel
 - 2.1.8. Galvanized steel back pan curtain wall

3. STRUCTURAL SYSTEM

3.1. THERM+ H-I 56

4. TYPICAL CORNER DETAILS

- 4.1. THERM+ H-I 56/60mm
 - 4.1.1. SPANDREL PANEL CORNER
 - 4.1.1.1. Wood column corner
 - 4.1.1.2. Insulated column corner
 - 4.1.1.3. 45° mullion corner
 - 4.1.2. SG2 corner (Structural glazing system)
 - 4.1.2.1. Corner with steel column
 - 4.1.2.2. Corner with wood column

5. TYPICAL DOOR DETAIL

- 5.1. Aluminum door Alumico
 - 5.1.1. Section detail Double glazing
 - 5.1.2. Section detail Triple glazing
 - 5.1.3. Plan detail Double glazing
- 5.2. Wood door Lemberc
 - 5.2.1. Section detail Triple glazing
 - 5.2.2. Plan detail Triple glazing
 - 5.2.3. Single wood lift and slide door (Standard) UNICEL ARCHITECTURAL CORP.
 - 5.2.4. Section detail Double glazing
 - 5.2.5. Plan detail Double glazing
 - 5.2.6. Section detail Triple glazing

Title :

5.2.7. Plan detail - Triple glazing

TABLE OF CONTENTS

UNICEL Pefining the Space Within* 540, Lucien-Thibodeau Portneuf, Qc, G0A 2Y0 Tel. 1.450.670.6844 Fax. 1.450.670.7144 Unicel@unicelarchitectural.com www.unicelarchitectural.com

UPDA	JTE :		
Nom :	J.PAUL-HUS	Date : 2021-06-10	1

Page :

DRAWING BY :

TABLE OF CONTENTS

5.4. Double wood lift and slide door (Standard) - UNICEL ARCHITECTURAL CORP.

- 5.4.1. Section detail Double glazing
- 5.4.2. Plan detail Double glazing
- 5.4.3. Section detail Triple glazing
- 5.4.4. Plan detail Triple glazing
- 5.5. Simple wood lift and slide door (Oversize) UNICEL ARCHITECTURAL CORP.
 - 5.5.1. Section detail Double glazing
 - 5.5.2. Plan detail Double glazing
 - 5.5.3. Section detail Triple glazing
 - 5.5.4. Plan detail Triple glazing
- 5.6. Double wood lift and slide door (Oversize) UNICEL ARCHITECTURAL CORP.
 - 5.6.1. Section detail Double glazing
 - 5.6.2. Plan detail Double glazing
 - 5.6.3. Section detail Triple glazing
 - 5.6.4. Plan detail Triple glazing

6. TYPICAL WINDOW DETAIL

- 6.1. Aluminum window Alumico
 - 6.1.1. Section detail Double glazing
 - 6.1.2. Section detail Triple glazing
 - 6.1.3. Plan detail Double glazing
- 6.2. Aluminum window Alumicor
 - 6.2.1. Section detail Double glazing
 - 6.2.2. Section detail Triple glazing
 - 6.2.3. Plan detail Double glazing
- 6.3. Wood window LEMBERC
 - 6.3.1. Section detail Triple glazing
 - 6.3.2. Plan detail Triple glazing
- 7. APPLICATIONS

7.1. Various

- 7.1.1. Plan detail Junction with masonry
- 7.1.2. Plan detail Junction with siding
- 7.1.3. Plan detail Junction with concrete wall
- 7.1.4. Section detail Exterior connector with insertion in concrete
- 7.1.5. Section detail Exterior connector without insertion in concrete
- 7.1.6. Section detail Double connector
- 7.1.7. Section detail Interior connector
- 7.1.8. Section detail Exterior connector with wood beam
- 7.1.9. Section detail Exterior connector with steel beam

7.2. Glass roof

- 7.2.1. Roof ridge connection
- 7.2.2. Intermediate roof connection
- 7.2.3. Eave section detail
- 7.2.4. Typical column & mullion

8. TRANSOM INSERTION

8.1. Insertion method

TABLE OF CONTENTS


UNICEL Pefining the Space Within* 540, Lucien-Thibodeau Portneuf, Qc, G0A 2Y0 Tel. 1.450.670.6844 Fax. 1.450.670.7144 Unicel@unicelarchitectural.com www.unicelarchitectural.com

itle	:		


 DRAWING BY :
 Page :


 M.LAVOIE
 Page :


 UPDATE :
 II





All rights reserved. These drawings are the property of UNICEL ARCHITECTURAL CORP.


























All rights reserved. These drawings are the property of UNICEL ARCHITECTURAL CORP.








CAUTION


Unicel Architectural Corp. don't recommend to use steel return on isolated back pans curtain wall. This method could result in a high risk of condensation at the edge of the adjacent glazing. They can create a thermal bridge and cool the aluminum base profile. We suggest to use rigid insulation at the perimeter of the isolated back pans curtain wall to compensate the glass thickness. We can also use exterior spandrel glass assembled in sealed units in front of the isolated back pans curtain wall.




































NOTE: THE MODEL OF WOOD LIFT AND SLIDE DOOR (STANDARD) IS ALSO AVAILABLE IN DOUBLE FORMAT .





All rights reserved. These drawings are the property of UNICEL ARCHITECTURAL CORP.


Page:


5.3









































































































All rights reserved. These drawings are the property of UNICEL ARCHITECTURAL CORP.




All rights reserved. These drawings are the property of UNICEL ARCHITECTURAL CORP.









CONVENTIONAL METHOD:

(INSIDE VIEW)




DIAGRAM 1: CONVENTIONAL TRANSOM INSERTION FROM THE INSIDE OF THE BUILDING TO THE OUTSIDE, WITH INVISIBLE MACHINING.

THE CURTAIN WALLS ARRIVES ON SITES IN PRE-ASSEMBLED MODULES, A FACADE CAN HAVE SEVERAL MODULES TO FACILITATE THE TRANSPORT. ONCE ON SITE, THE ASSEMBLY MUST BE FINALIZED BY INSERTING THE CONNECTING TRANSOMS BETWEEN THE SECTIONS. IT MAY OCCUR THAT THEY COME INTO CONFLICT WITH STRUCTURAL ELEMENTS LIKE COLUMNS, BEAMS, WALLS, ETC. UNLIKE THE CONVENTIONAL METHOD, THE TRANSOMS MUST BE INSTALLED FROM THE OUTSIDE OF THE BUILDING. TO ALLOW THIS, THE TRANSOMS CONNECTORS MUST BE MILLED FROM ONE SIDE TO THE OTHER. WOOD BLOCKS HIDE THE CONNECTORS FROM THE BUILDING.

SPECIAL METHOD:

